

## GOODSENSE brand multi-functional forklift truck FD30 FD35 FD40

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Brand Name: Goodsense
- Model Number: FD30
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Bare packaging
- Delivery Time: 30-40work days
- Payment Terms: T/T



#### Product Specification

- Model Number: FD30 FD35 FD40
- Rated Loading Capacity: 3 Ton 4 TON 3.5 TON
- Core Components: Bearing, Pump, Gearbox, Engine
- Weight (KG): 4250 Kg
- Fork Length: 1070mm
- Fork Width: 125mm
- Overall Dimensions: 2780\*1230\*2115mm
- Engine: Chinese Engine
- Place Of Origin: China
- Brand Name: Goodsense
- Name: Forklift
- Condition: New
- Energy Supply: Reference Introduction
- Advantage: Small Vibration And Noise
- Highlight: **goodsense diesel forklift truck,**



### Products Show

- 1.Wide view mast design, ensure the driver has an excellent view, which makes loading and unloading operations more secure and efficient;
- 2.Load sensing priority steering hydraulic system design, flexible steering, mast lift speed increased by 20%;
- 3.All accessories like engine, gear box are support by domestic and world famous brand, high quality, reliable after-sales;
- 4.The overhead guard adopts the high strength steel sheet to press molding, providing more sophisticated security for the driver, it can also prevent wind and rain.

| Model                                    |      | FD30           | FD35        | FD40         |
|------------------------------------------|------|----------------|-------------|--------------|
| Rated lifting load                       | kg   | 3000           | 3500        | 4000         |
| Load center distance                     | mm   | 500            |             |              |
| Free lifting height                      | mm   | 160            |             |              |
| overall length<br>(Withfork/Withoutfork) | mm   | 3752/2682      | 3763/2693   | 4000/2930    |
| Width                                    | mm   | 1225           |             | 1290         |
| Overhead guard height                    | mm   | 2090           |             | 2180         |
| Wheelbase                                | mm   | 1700           |             | 1900         |
| Minimum ground clearance                 | mm   | 135            |             | 140          |
| Mast tilt angle (front/rear)             | %    | 6° /12°        |             |              |
| Tire no. (before)                        |      | 28*9-15-14PR   |             | 250-15-16PR  |
| Tire no. (after)                         |      | 6.5-10-1OPR    |             | 7.00-12-12PR |
| Minimum turning radius (outer side)      | mm   | 2400           | 2420        | 2710         |
| Minimum right angle aisle width          | mm   | 4260           | 4260        | 4750         |
| Fork size                                | mm   | 1070*125*45    | 1070*125*50 | 1070*150*50  |
| maximum working speed(Full-load/No-load) | km/h | 18/19          | 19/19       |              |
| maximum lifting speed(Full-load/No-load) | mm/s | 440/480        | 330/370     |              |
| maximum gradeability(Full-load/No-load)  | %    | 15/20          |             |              |
| Forklift weight                          | kg   | 4250           | 4500        | 4950         |
| Engine model                             |      | Chinese engine |             |              |



**Taizhou Ruidong Import and Export Co., Ltd**



18367688514



gjq\_0208@163.com



rdforklift.com

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China